



## Environmental GlideWall Kit

Part # 14-1017xx

Environmental Kit is supplied in 15 mil translucent off-white reinforced vinyl (SC-10)

	<b>Translucent Laminated Polyester Vinyl</b>	<b>Hem Chain</b>	<b>Velcro</b>	<b>Thread</b>
<b>Material</b>	Polyester Weft Lock Scrim laminated between 2 layers of PVC	Zinc Plated Steel	Woven Nylon	Nylon
<b>Weight</b>	13 oz / sq yd	.25 lb/ft	.019 oz/sq in	6140 yds/lb
<b>Thickness</b>	13 mils	½"	.013"	.010"
<b>Flammability</b> *NFPA-701	Pass	N/A	N/A	N/A
*California State Fire Marshall F-191	Pass	N/A	--	--
*MVSS - *302	Pass	N/A	Pass	--
<b>Temperature Limits</b>	-10 to +160F	N/A	-20 to + 3,212F	-20 to +445F
<b>Acid Resistance</b>	Good	Excellent	Good	Excellent
<b>UV Resistance</b>	UV Inhibitor	N/A	Good	Good
<b>Mildew &amp; Rot Resistance</b>	Mildew Inhibitor	N/A	Good	Good

Note: This GlideWall System is not recommended or warranted for outdoor use. Panels are warranted for 5 years from date of purchase for materials and workmanship. At its election, Singer Safety Company may choose to repair or replace defective materials, but shall in no event exceed the purchase price of the particular goods.

This information is based on data believed to be accurate. As conditions of product use are beyond our control, Uni-Glide or Singer Safety Company makes no warranties, expressed or implied, in connection with the use of this information. Evaluation should be made by the user to determine the suitability of this product for specific applications. Uni-Glide, a division of Singer Safety Company will not be liable for loss or damage arising from the use or misuse of this product.