



Modular Acoustic Screen


½ lb Loaded Vinyl with 1" Double Sided QFM

Part# 22-210248 (double sided)

Color: Metallic Gray or White

Weight: 60 lbs

Thickness: 1" thick (each side), 2 lb./cu. Ft. density fiberglass batting, quilted with Polyester thread to an aluminum-vinyl coated fiberglass facing cloth. Stitched nylon thread to a ½ lb sq. ft. 85 mil thick, PVC mass-loaded vinyl sulfate barrier backing.



Size: 48" Wide Quilted Fiberglass with facing
54" Wide Mass-Loaded vinyl barrier backing
2" Wide Velcro Fastener stitched to vertical edges on Modular Panels

Frame: 1" round tubular 18 gauge steel – Black enamel finish

Chemical Resistivity: Resists oils, grease, dirt, dust, mild acids and alkalis.

Flame Resistance:

QFM Facing – Class 1 rated per ASTM E84-70:

<u>Flame spread</u>	<u>Fuel Contributed</u>	<u>Smoke Developed</u>
5.0	20.00	5.0

Mass-loaded barium sulfate barrier backing – Per Federal Test Standard 191, Method 5903:3

<u>Flameout</u>	<u>Afterglow</u>	<u>Char Length</u>
0.0 sec	1.0 sec	0.4 inches

Clean ability: Facing and Barrier can be steam cleaned or washed with common industrial cleaners.

Temperature

Limits: Service range -20° to +180°F (continuous)

Noise Transmission Loss:

		Frequency (Hertz)					
125	250	500	1000	2000	4000	STC	
10dB	16dB	23dB	28dB	31dB	37dB	25dB	

(Per ASTM E90-75 and ASTM E413-73)

This information is based on data believed to be accurate. As conditions of product use are beyond our control, Singer Safety Company makes no warranties expressed or implied, in connection with the use of this information. Evaluation should be made by the distributor and/or user to determine the suitability of this product for specific applications. Singer Safety Company will not be liable for loss or damage arising from the use or misuse of this product.