

## Specialty Laminated Vinyl

Translucent Vinyl Laminated Polyester

<b>Part #</b>	15-001072 (SC-10)		
<b>Colors</b>	Translucent Off White		
<b>Thickness</b>	15 mils		
<b>Finished Square Yard Weight</b>	16 oz		
<b>Roll Size</b>	61"W x 100 yds		
<b>Base Material</b>	Woven 8 x 5 count 500/1000 denier polyester weft-loc scrim		
<b>Construction</b>	Polyester scrim completely laminated between two layers of flame retardant PVC (vinyl).		
<b>Strength</b>	<u>Warp (lb.)</u>	<u>Fill (lb.)</u>	<u>Method</u>
<b>Tensile</b>	128	120	Fed. Std. 191, 5100.1
<b>Tear</b>	40	46	
<b>Mullen Burst</b>	180 lb./sq. in.		
<b>Product Characteristics</b>	Tear resistant, excellent material for thermal isolation of large areas without blocking illumination.		
<b>Flame Resistance</b>	Meets or exceed requirements of the following flame resistance tests;		
	<u>Organization</u>	<u>Test</u>	
	Federal Test Std. (GSA)	191A, Meth. 5903	
	California Fire Marshall	Sec. 1237.1	
	National Fire Protection Assoc	701	
	ASTM	E-84 Class A	
<b>Temperature Limits</b>	Service Range of -10°F to +160°F		