

Specialty Laminated Vinyl

Vinyl Coated Polyester

Part #	15-000261WH (SC-2WH)		
Color	White		
Thickness	17 mils		
Finished Square Yard Weight	18 oz		
Roll Size	61" W x 100 Yds		
Base Material	5 oz psy Polyester (1000D x 1300D) Fiber, woven.		
Product Characteristics	Poly Vinyl Chloride 60% coated front & 40% coated back is mildew & Ultra Violet resistant. Sealed properties; dielectric & thermal.		
Flame Resistance	<u>Results</u>	<u>Test Method</u>	
Time of After flame	1 sec	5903	
NFPA 701 (small scale)	Pass	N/A	
Initial CPAI-84	Pass	N/A	
ASTM E 84 Class A	Pass	N/A	
Strength	<u>Warp</u>	<u>Fill</u>	<u>Method</u>
Grab Tensile	400 lb./in.	390 lb./in.	ASTM D5034/Fed Std 191A-5100
Strip Tensile	290 lb./2 in.	280 lb./2 in.	ASTM D5035/Fed Std 191A-5102
Tongue Tear	90 lbs	85 lbs	ASTM D751/Fed Std 191A-5134
Adhesion	1" Adhesive	10 lbs	
Abrasion	<u>Wheel:H-18</u>	<u>Test Method</u>	
	1,000 Cycle, 70 rpm	ASTM D3884/Fed Std 191A-5106	
	Load: 1,000 gr		
Temperature Limits	-40°F		