



## SOUND STICK ADHESIVE TUBE

<b>Part Number:</b>	15-015010								
<b>Color:</b>	White								
<b>Weight:</b>	10.5 oz per Tube								
<b>Viscosity:</b>	130,000 cps								
<b>Roll Size:</b>	48" wide, 20 YDS. Long								
<b>Base Material:</b>	Cross-linking polymer / medium viscosity mastic								
<b>Freeze/Thaw Stability:</b>	Passes three cycles								
<b>Storage Life:</b>	One year in unopened container at 75°F								
<b>Application Temperature:</b>	30°F to 100°F								
<b>Service Temperature:</b>	10°F to 120°F								
<b>Method of Application:</b>	Gunning from tube								
<b>Open Time:</b>	30 Minutes								
<b>Coverage:</b>	Approximate length of bead according to bead diameter <table><tr><td><u>1/8"</u></td><td><u>1/4"</u></td><td><u>3/8"</u></td></tr><tr><td>129 ft.</td><td>32 ft.</td><td>14 ft.</td></tr></table>	<u>1/8"</u>	<u>1/4"</u>	<u>3/8"</u>	129 ft.	32 ft.	14 ft.		
<u>1/8"</u>	<u>1/4"</u>	<u>3/8"</u>							
129 ft.	32 ft.	14 ft.							
<b>Cleanup:</b>	Clean with water while adhesive is still wet. Scrape dried excess.								
<b>Strength Data:</b>	<table><thead><tr><th><u>Drying Time</u></th><th><u>Strength Development</u></th></tr></thead><tbody><tr><td>2 hrs</td><td>346 lbs</td></tr><tr><td>24 hrs</td><td>1100 lbs</td></tr><tr><td>7 Days</td><td>1300 lbs</td></tr></tbody></table>	<u>Drying Time</u>	<u>Strength Development</u>	2 hrs	346 lbs	24 hrs	1100 lbs	7 Days	1300 lbs
<u>Drying Time</u>	<u>Strength Development</u>								
2 hrs	346 lbs								
24 hrs	1100 lbs								
7 Days	1300 lbs								
<b>Working Surfaces:</b>	Formulated specifically as an environmentally safe solution to AFG-01 type construction applications. Develops a strong bond in a matter of hours when used on plywood, paneling, hardboard, and gypsum wallboard. Also bonds homasote, glass, cultured marble, brick, corian, polyurethane foam, polystyrene foam, and most other porous substrates. Should not be used on plastic, tub kits, and vinyl surfaces.								