



## SuperVision GlideWall Kit

Part # 14-0717xx

SuperVision Panels are supplied with one color below the see-through section and another color above the see-through section. This kit is available in opaque 14 mil thick vinyl.

Colors available: white, black, gray, yellow, green, blue, red or orange.

	<b>Translucent Laminated Polyester Vinyl</b>	<b>Clear PVC Window</b>	<b>Hem Chain</b>	<b>Velcro</b>	<b>Thread</b>
<b>Material</b>	Polyester Weft Lock Scrim laminated between 2 layers of PVC	Double Polished Clear PVC	Zinc Plated Steel	Woven Nylon	Nylon
<b>Weight</b>	13 oz / sq yd	12 oz/ sq yd	.25 lb/ft	.019 oz/sq in	6140 yds/lb
<b>Thickness</b>	14 mils	16 mils	½"	.013"	.010"
<b>Flammability</b> *NFPA-701	Pass	Pass	N/A	N/A	N/A
*California State Fire Marshall F-191	Pass	Pass	N/A	--	--
*MVSS - *302	--	--	N/A	Pass	--
<b>Temperature Limits</b>	-10 to +160F	-20 to +160F	N/A	-20 to + 3,212F	-20 to +445F
<b>Acid Resistance</b>	Good	Good	Excellent	Good	Excellent
<b>UV Resistance</b>	UV Inhibitor	UV Inhibitor	N/A	Good	Good
<b>Mildew &amp; Rot Resistance</b>	Mildew Inhibitor	Excellent	N/A	Good	Good

Note: This GlideWall System is not recommended or warranted for outdoor use. Panels are warranted for 5 years from date of purchase for materials and workmanship. At its election, Singer Safety Company may choose to repair or replace defective materials, but shall in no event exceed the purchase price of the particular goods.

This information is based on data believed to be accurate. As conditions of product use are beyond our control, Uni-Glide or Singer Safety Company makes no warranties, expressed or implied, in connection with the use of this information. Evaluation should be made by the user to determine the suitability of this product for specific applications. Uni-Glide, a division of Singer Safety Company will not be liable for loss or damage arising from the use or misuse of this product.