



WeldVision GlideWall Kit

Part # 14-06xxxx

WeldVision Panels are supplied with one color below the tinted see-through section and another color above the tinted see-through section. This kit is available in opaque 14 mil thick vinyl.

Colors available in opaque: white, black, gray, yellow, green, blue, red or orange

Colors available in Trans-Vue (tinted): smoke gray, yellow, green, blue or orange

	Translucent Laminated Polyester Vinyl	Tinted PVC Window	Hem Chain	Velcro	Thread
Material	Polyester Weft Lock Scrim laminated between 2 layers of PVC	Tinted PVC	Zinc Plated Steel	Woven Nylon	Nylon
Weight	13 oz / sq yd	13 oz/ sq yd	.25 lb/ft	.019 oz/sq in	6140 yds/lb
Thickness	14 mils	14 mils	½"	.013"	.010"
Flammability *NFPA-701	Pass	Pass	N/A	N/A	N/A
*California State Fire Marshall F-191	Pass	Pass	N/A	--	--
*MVSS - *302	--	--	N/A	Pass	--
Temperature Limits	-10 to +160F	-10 to +160F	N/A	-20 to + 3,212F	-20 to +445F
Acid Resistance	Good	Good	Excellent	Good	Excellent
UV Resistance	UV Inhibitor	UV Inhibitor	N/A	Good	Good
Mildew & Rot Resistance	Mildew Inhibitor	Excellent	N/A	Good	Good

Note: This GlideWall System is not recommended or warranted for outdoor use. Panels are warranted for 5 years from date of purchase for materials and workmanship. At its election, Singer Safety Company may choose to repair or replace defective materials, but shall in no event exceed the purchase price of the particular goods.

This information is based on data believed to be accurate. As conditions of product use are beyond our control, Uni-Glide or Singer Safety Company makes no warranties, expressed or implied, in connection with the use of this information. Evaluation should be made by the user to determine the suitability of this product for specific applications. Uni-Glide, a division of Singer Safety Company will not be liable for loss or damage arising from the use or misuse of this product.